

SDS Ref: 71 Revision 1 Revision Date: 26.03.2018

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

1.1.1 TOduct fuction	
Product name	CUTTING & TAPPING LUBRICANT 380ML
Product No.	237159

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Supplier

T.I. Midwood & Co. Ltd TIMco House Green Lane Wardle Nantwich CW5 6BJ 01829 261111

1.4. Emergency telephone number

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical and Chemical Hazards Human health Environment

Flam. Aerosol 1 - H222 Lact. - H362 Aquatic Chronic 2 - H411

2.2. Label elements

2.3. Other hazards

Label In Accordance With (EC) No. 1272/2008

Label In Accordance With (EC) No. 1	272/2008	¥2
Signal Word	Danger	
Hazard Statements	11000	
	H222	Extremely flammable aerosol.
	H362	May cause harm to breast-fed children.
	H411	Toxic to aquatic life with long lasting effects.
Precautionary Statements		
	P102	Keep out of reach of children.
	P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
	P263	Avoid contact during pregnancy/while nursing.
	P261	Avoid breathing vapour/spray.
	P271	Use only outdoors or in a well-ventilated area.
	P302+352	IF ON SKIN: Wash with plenty of soap and water.
		P501 Dispose of contents/container in accordance with local regulations.
Supplementary Precautionary State	ments	
	P211	Do not spray on an open flame or other ignition source.
	P251	Pressurized container: Do not pierce or burn, even after use.
	P270	Do not eat, drink or smoke when using this product.
	P308+313	IF exposed or concerned: Get medical advice/attention.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures			
BUTANE			1-5%
CAS-No.: 106-97-8	EC No.: 203-448-7		
Classification (EC 1272/20	008)	Classification (67/548/EEC)	
Flam. Gas 1 - H220		F+;R12	
CHLORINATED PARAFFIN	C14-C17 (51%)		10-30%
CAS-No.: 85535-85-9	EC No.: 287-477-0		
Classification (EC 1272/20	008)	Classification (67/548/EEC)	
EUH066		N;R50/53.	
Lact H362		R64,R66.	
Aquatic Acute 1 - H400			
Aquatic Chronic 1 - H410			
ISOBUTANE			1-5%
CAS-No.: 75-28-5	EC No.: 200-857-2		
Classification (EC 1272/20	008)	Classification (67/548/EEC)	
Flam. Gas 1 - H220		F+;R12	
	and Hazard Statements are Displayed	Lin Continue 10	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General information

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

Inhalation

Move the exposed person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Keep the affected person warm and at rest. Get prompt medical attention.

Indestion

DO NOT INDUCE VOMITING! Rinse mouth thoroughly with water and give large amounts of milk or water to people not unconscious. Get medical attention if any discomfort continues.

Skin contact

Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

Eye contact

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

General information NOTE! Effects may be delayed. Keep affected person under observation.

4.3. Indication of any immediate medical attention and special treatment needed

No specific first aid measures noted.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Extinguishing media Use: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

5.2. Special hazards arising from the substance or mixture

Unusual Fire & Explosion Hazards Aerosol cans may explode in a fire.

5.3. Advice for firefighters

Special Fire Fighting Procedures Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours. 2 of 5

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

6.2. Environmental precautions

6.3. Methods and material for containment and cleaning up

Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Let evaporate. Keep out of confined spaces because of explosion risk. If leakage cannot be stopped, evacuate area.

6.4. Reference to other sections

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

7.2. Conditions for safe storage, including any incompatibilities

Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

7.3. Specific end use(s)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	STD	TWA	- 8 Hrs	STEL -	15 Min	Notes
BUTANE	WEL	600 ppm	1450 mg/m3	750 ppm	1810 mg/m3	

WEL = Workplace Exposure Limit.

8.2. Exposure controls

Protective equipment



Engineering measures

Provide adequate general and local exhaust ventilation.

Respiratory equipment

No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit. Use chemical cartridge protection with appropriate cartridge.

Hand protection

Use protective gloves.

Eye protection

Use approved safety goggles or face shield.

Other Protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

Hygiene measures

DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance	Aerosol.
Colour	Typical
Odour	Characteristic.
Flammability Limit - Lower(%)	0.8
Flammability Limit - Upper(%)	9.0

9.2. Other information

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

No specific reactivity hazards associated with this product.

10.2. Chemical stability

Stable under normal temperature conditions.

10.3. Possibility of hazardous reactions

Not known.

10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition. Avoid contact with: Strong oxidising agents. Strong alkalis. Strong mineral acids.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Inhalation

May cause irritation to the respiratory system. Vapours may cause headache, fatigue, dizziness and nausea. Prolonged inhalation of high concentrations may damage respiratory system.

Ingestion

May cause discomfort if swallowed. May cause stomach pain or vomiting. Gastrointestinal symptoms, including upset stomach.

Skin contact Prolonged or repeated exposure may cause severe irritation. Acts as a defatting agent on skin. May cause cracking of skin, and eczema.

Eye contact Irritating to eyes. May cause chemical eye burns. Route of entry Inhalation. Skin and/or eye contact.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

Dangerous for the environment if discharged into watercourses.

12.1. Toxicity

Data set not currently available.

12.2. Persistence and degradability

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

Not known.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements.

SECTION 14: TRANSPORT INFORMATION

14.1. UN number	
UN No. (ADR/RID/ADN)	1950
UN No. (IMDG)	1950
UN No. (ICAO)	1950
14.2. UN proper shipping name	
Proper Shipping Name	AEROSOLS

14.3. Transport hazard class(es)

ADR/RID/ADN Class
ADR/RID/ADN Class
ADR Label No.
IMDG Class
ICAO Class/Division
Transport Labels

2 Class 2: Gases 2.1 2.1 2.1



14.4. Packing group

ADR/RID/ADN Packing group IMDG Packing group ICAO Packing group Not Applicable Not Applicable Not Applicable

14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant No.

14.6. Special precautions for user EMS F-

F-D, S-U

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Statutory Instruments The Aerosol Dispensers (Amendment) Regulations 2014 No.1130 Approved Code Of Practice Classification and Labelling of Substances and Preparations Dangerous for Supply. Guidance Notes Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. EU Legislation Regulation (EC) No.1272/2008 The Classification, Labelling and Packaging of substances and mixtures Regulations Regulation (EC) No. 1907/2006 The Registration, Evaluation, Authorisation and Restriction of Chemicals Regulations (REACH) 2001/95/EC The General Product Safety Directive (GPSD) Commission Regulation (EU) 2015/830 Requirements for the compilation of safety data sheets (amending REACH) Authorisations (Title VII Regulation 1907/2006) No specific authorisations are noted for this product. Restrictions (Title VIII Regulation 1907/2006) No specific restrictions of use are noted for this product.

15.2. Chemical Safety Assessment

SECTION 16: OTHER INFORMATION

Revision Date	26.03.2018
Revision	1
Hazard Statements In Full	
EUH066	Repeated exposure may cause skin dryness or cracking.
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H362	May cause harm to breast-fed children.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.